

DLI-1319





Descrizione

Nella stampa digitale di oggetti dalle *geometrie complesse*, il posizionamento manuale con dime o maschere rallenta la produzione e introduce margini di errore. La stampante **UV DLI-1319** supera questo limite integrando un sistema di posizionamento visivo che riconosce *automaticamente* la forma del supporto, eliminando la necessità di cornici di allineamento e aprendo la produzione a materiali irregolari senza i tempi e i costi delle attrezzature dedicate.

Cuore di questa automazione è il sistema di visione ottica CIS montato su un design a doppia trave indipendente con doppio motore lineare.



Mode of Equipment	DLI-1319
Print Head Type	RIICOH G5/G6/G5S
Operation Environment	Temperature: 20°C- 30 °C/Humidity: 50-70%
Print Height	0-200mm (could be customized)
Data Interface	Gigabit network interface
Driver Software	Microsoft Windows 10 Pro
Printing Color	P+W+CMYKLCMLYLK+V(Support a variety of color combinations)
Printer Weight	1300kg (intelligent carriage visual positioning function)
Ink System	Continuous supply/ink 2000ml/subtank constant temperature and pressure/white auto stirring
Printing Size	Belt Printer Mode 1300×infinite
Print Head Quantity	2-8 (could be customized)
Printing Precision	960×900DPI/920×1200DPI/960×1800DPI
Printing Mode	stepping and printing in a cycle stepping mode
File Format	TIFF(RGB&CMYK)BMP、PDF、EPS、JPEG、etc.
Power Requirements	8000W
Printer Dimension	3385×2180×1500mm
RIP Software	Riprint
4pass	One-way: 14.4 m²/h / Two-way: 23.76 m²/h
6pass	One-way: 9.86 m²/h / Two-way: 17.74 m²/h
8pass	One-way: 6.41 m²/h / Two-way: 14.6 m²/h