

DLI-1612





Descrizione

Quando il formato di stampa cresce ma lo spazio in produzione resta prezioso, serve una macchina che unisca un'area di lavoro estesa a un ingombro contenuto. La *stampante piana UV DLI-1612* risponde con un piano da *1,6 metri per 1,2 metri* e un corpo compatto, progettato per integrarsi nei flussi di lavoro di aziende grafiche. La capacità di eseguire la stampa sincrona di bianco e vernice lucida, unita a un'alta risoluzione nativa, la rende una piattaforma flessibile per **pannelli, lastre e oggetti piani** di diverso spessore, mantenendo stabilità ed efficienza anche nelle lavorazioni a ciclo continuo.



Mode of Equipment	DLI-1612
Print Head Quantity	2-8 (could be customized)
Printing precision	20×900DPI / 720×1200DPI / 720×1800DPI
Printing height	0-100mm (could be customized)
Driver Software	Microsoft Windows 10 Pro
Printer Dimension	3690 × 2080 × 1450
RIP Software	ColorGATE RIP, PhotoPrint, RIIN etc...
Printer Weight	1450kg (weights are different from different configuration)
Ink System	Continuous Supply / tank 2000ml / subtank for temperature and pressure / white auto-stirring
Lifting Function	Carriage auto electrical height adjustment/Manual intelligent carriage height adjustment
Printing Size	1200 × 1600mm
Print Head Type	Ricoh G5/G5/G6 Epson i1600/i3200
Printer Color	CMYK + LC LM + W + V (Support a variety of color combinations)
File Format	TIFF (RGB & CMYK) BMP, PDF, EPS, JPEG etc...
Power Requirements	AC220V(±10%); 50HZ; P:6000W
Operation Environment	temperature: 20°C-30°C / Humidity: 40%-70%
Data Interface	High Speed USB transfer interface / Gigabit network interface
4pass	Single Gen5: 27 m²/h / Single Gen6: 35 m²/h / Double Gen5: 42 m²/h / Double Gen6: 52 m²/h
6pass	Single Gen5: 18 m²/h / Single Gen6: 24.63 m²/h / Double Gen5: 30 m²/h / Double Gen6: 39 m²/h
8pass	Single Gen5: 14 m²/h / Single Gen6: 18 m²/h / Double Gen5: 21 m²/h / Double Gen6: 33 m²/h