

DLI-2500





Descrizione

Per i laboratori e le aziende di stampa che gestiscono quotidianamente formati **extra-large**, la differenza tra un collo di bottiglia e una produzione fluida spesso risiede nella *larghezza del piano di lavoro*. La stampante **DLI-2500** affronta questa esigenza con un piano a **nastro mesh ultra largo**, aprendo possibilità applicative che vanno ben oltre i formati *standard*. La base del sistema è un **telaio** interamente in *acciaio* con molteplici punti di supporto densi e ravvicinati, una configurazione *monolitica* che mira a mantenere la geometria della macchina stabile anche sotto i carichi di lavoro più intensivi.



Mode of Equipment	DLI-2500
Print head type	Konica 1024i print head/Ricoh G5 /Ricoh G6 print head
Printing color	CMYK+LCLM+W+V(Support a variety of color combinations)
Printing Height	0-50mm (can be customized)
Printing Precision	720*900DPI/720*1200DPI/720*1800DPI
Lifting function	Automatic lifting of print head / automatic monitoring of print height
Ink System	Continuous supply/ink 2000ml/subtank constant temperature and pressure/white auto stirrer
RIP Software	ColorGATE RIP Photo print Rprint, and supporting various printing softwares
Data interface	High speed USB transfer interface/Gigabit network interface
Driver Software	Microsoft Windows 10
Operation Environment	Temperature: 20°C - 30 °C / Humidity: 40-70%
Printer Weight	2300KG
Printing Size	Plate: 2500×2000mm / Coil: 2500mm(max)
Print head quantitiy	4-18(And can be customized)
Curing system	UV lamp curing
File format	TIFF(RGB&CMYK)BMP、PDF、EPS、JPEG、etc.
Power requirements	AC220V(±10%); 50HZ;P:8000W
Printer Dimension	5300×1660×1550mm
4pass	Single Row: 32 m²/h / Two Row: 56 m²/h / Three Row: 72 m²/h / Three Row Ricoh: 65 m²/h
6pass	Single Row: 25 m²/h / Two Row: 42 m²/h / Three Row: 60 m²/h / Three Row Ricoh: 48 m²/h
8pass	Single Row: 18 m²/h / Two Row: 30 m²/h / Three Row: 48 m²/h / Three Row Ricoh: 32 m²/h