

DLI-3300





Descrizione

Nel panorama della **stampa digitale di grande formato**, la possibilità di lavorare in un'unica soluzione sia supporti *rigidi* sia materiali in rotolo segna un salto di efficienza concreto. La **stampante UV ibrida DLI-3300** incarna questa convergenza: una macchina a nastro di livello industriale con una **larghezza di stampa di 3,3 metri** e una piattaforma integrata che accoglie pannelli *rigidi* e bobine *flessibili*, riducendo la necessità di attrezzature separate e ampliando il ventaglio di applicazioni gestibili con un solo investimento.



Mode of Equipment	DLI-3300
File Format	TIFF (RGB & CMYK) BMP, PDF, EPS, JPEG etc...
Printing Height	0-50mm
Standard Solution	CMYK
Printer Size	Roll Material 3250mm (max)
Print Head Quantity	4-32 (could be customized)
Printhead	Konica 1024i
Conveyor Belt	Mesh Belt
Data Interface	High Speed USB transfer interface / Gigabit network interface
Operation Environment	temperature: 20°C-30°C / Humidity: 40%-70%
Printer Color	CMYK + LM + LC + W + V (support a variety color combinations)
Lifting Function	Automatic Lifting of the print head / automatic motoring of print height
Ink System	Continuous ink Supply / ink tank 2000ml / subtank temperature and pressure / white auto-stirrer
RIP Software	ColorGATE RIP, PhotoPrint, RIIN, and supporting various printing software
Print Weight	2500kg (weights are different from different configurations)
Curing System	UV Lamp curing
Driver Software	Microsoft Windows 10 Pro
Power Requirements	AC220V(±10%); 50HZ; P:8000W
Printer Dimension	4500×1400×1500
Printing precision	720×900DPI / 720×1200DPI / 720×1800DPI